



2 SOFFIT DETAIL
A-6.0 / 3/4" = 1'-0"

REFLECTED CEILING PLAN LEGEND

NOTES
REFER TO M.E.P. DRAWINGS FOR EXACT QTY. AND LOCATION OF MECH., ELEC., AND FIRE-PROTECTION WORK. PROVIDE SLOTTED CHANNEL FRAMING SUPPORTS FOR CEILING MOUNTED ITEMS.
TYPICAL:
FULL HEIGHT DRYWALL (NON-RATED)
SMOKE TIGHT
ONE HOUR RATING
NEW GYPSUM BOARD CEILING / SOFFIT
EXISTING GYPSUM BOARD CEILING / SOFFIT
2x2 ACOUSTIC PANEL CEILING
ROLLER SHADE
PENDANT MOUNT FLUORESCENT LIGHT FIXTURE
2x2 RECESSED FLUORESCENT LIGHT FIXTURE
2x4 RECESSED FLUORESCENT LIGHT FIXTURE
RECESSED DOWNLIGHT
LINEAR FLUORESCENT LIGHT FIXTURE (IN GRID & PENDANT MOUNT)
1x4 SURFACE MOUNTED FLUORESCENT LIGHT FIXTURE
4' SURFACE MOUNTED STRIP LIGHT FIXTURE
COVE LIGHT
PENDANT WALL WASH

GENERAL NOTES
1. SEE A-1.0 FOR ACCESSORY SCHEDULE.
2. CLEAN, REPAIR, PREPARE, AND PAINT ALL GYPSUM BOARD SOFFIT AND CEILING SURFACES.
3. CEILING AND SOFFIT SURFACES MAY BE PAINTED A DIFFERENT COLOR THAN ADJACENT WALL COLOR.
4. VERIFY EXISTING SUBSTRATES ARE DRY AND FREE FROM LEAKS BEFORE REPAIRING GYPSUM BOARD SURFACES OR INSTALLING NEW CEILING FINISHES. NOTIFY ARCHITECT IF LEAKS, OR WET SURFACES ARE DISCOVERED.
5. ALL WALLS ARE FULL HEIGHT EXCEPT AS NOTED OTHERWISE.
6. SEE MECHANICAL, ELECTRICAL AND PLUMBING SHEETS FOR ALL MEP ITEMS. ALL MEP ITEMS SHOWN ON THE REFLECTED CEILING PLANS ARE FOR REFERENCE ONLY AND SHOULD NOT BE USED FOR CONSTRUCTION.

LEGEND ITEMS:
HIGH VOLUME FAN
WALL MOUNTED LIGHT FIXTURE
WALL MOUNTED EXIT LIGHT FIXTURE
CEILING MOUNTED EXIT LIGHT FIXTURE
2x2 RETURN AIR GRILL
1x1 RETURN AIR GRILL
2x2 SUPPLY DIFFUSER
1x1 SUPPLY DIFFUSER
ACOUSTICAL CEILING MOUNTED POWER DROP. SEE ELECTRICAL DWGS.
TRACK LIGHT
WALL WASHER