


REFLECTED CEILING PLAN LEGEND

- NOTES**
 REFER TO M.E.P. DRAWINGS FOR EXACT QTY. AND LOCATION OF MECH., ELEC., AND FIRE PROTECTION WORK. PROVIDE SLOTTED CHANNEL FRAMING SUPPORTS FOR CEILING MOUNTED ITEMS. TYPICAL:
 FULL HEIGHT DRYWALL (NON-RATED) SMOKE TIGHT
 ONE HOUR RATING
 NEW GYPSUM BOARD CEILING / SOFFIT
 EXISTING GYPSUM BOARD CEILING / SOFFIT
 2x2 ACOUSTIC PANEL CEILING
 ROLLER SHADE
 PENDANT MOUNT FLUORESCENT LIGHT FIXTURE
 2x2 RECESSED FLUORESCENT LIGHT FIXTURE
 2x4 RECESSED FLUORESCENT LIGHT FIXTURE
 RECESSED DOWNLIGHT
 LINEAR FLUORESCENT LIGHT FIXTURE (IN GRID & PENDANT MOUNT)
 1x4 SURFACE MOUNTED FLUORESCENT LIGHT FIXTURE
 4' SURFACE MOUNTED STRIP LIGHT FIXTURE
 COVE LIGHT
 PENDANT WALL WASH
- GENERAL NOTES**
 1. SEE A-1.0 FOR ACCESSORY SCHEDULE.
 2. CLEAN, REPAIR, PREPARE, AND PAINT ALL GYPSUM BOARD SOFFIT AND CEILING SURFACES.
 3. CEILING AND SOFFIT SURFACES MAY BE PAINTED A DIFFERENT COLOR THAN ADJACENT WALL COLOR.
 4. VERIFY EXISTING SUBSTRATES ARE DRY AND FREE FROM LEAKS BEFORE REPAIRING GYPSUM BOARD SURFACES OR INSTALLING NEW CEILING FINISHES. NOTIFY ARCHITECT IF LEAKS, OR WET SURFACES ARE DISCOVERED.
 5. ALL WALLS ARE FULL HEIGHT EXCEPT AS NOTED OTHERWISE.
 6. SEE MECHANICAL, ELECTRICAL AND PLUMBING SHEETS FOR ALL MEP ITEMS. ALL MEP ITEMS SHOWN ON THE REFLECTED CEILING PLANS ARE FOR REFERENCE ONLY AND SHOULD NOT BE USED FOR CONSTRUCTION.



- HIGH VOLUME FAN
 WALL MOUNTED LIGHT FIXTURE
 WALL MOUNTED EXIT LIGHT FIXTURE
 CEILING MOUNTED EXIT LIGHT FIXTURE
 2x2 RETURN AIR GRILL
 1x1 RETURN AIR GRILL
 2x2 SUPPLY DIFFUSER
 1x1 SUPPLY DIFFUSER
 ACOUSTICAL CEILING MOUNTED POWER DROP. SEE ELECTRICAL DWGS.
 TRACK LIGHT
 WALL WASHER

1 1ST LEVEL REFLECTED CEILING PLAN
 A-6.1 1/8" = 1'-0"