

GENERAL NOTES (APPLICABLE TO ALL WORK AND DOCUMENTS)

1. ALL ELECTRICAL COMPONENTS AND EQUIPMENT SHALL BE LABELED BY UNDERWRITERS LABORATORIES OR OTHER LISTED LISTING AGENCY (APPROVED AND LABELING OF REMOVAL COMPONENTS ON AN ASSEMBLY IS NOT ACCEPTABLE AS MEANS THE REQUIREMENT) UNLESS SHOWN BY THE ENGINEER IN WRITING.
2. ALL WIRING SYSTEMS SHALL BE INSTALLED WITH A MINIMUM OF SERVICE CONDUCTORS, WHETHER SINGLE OR PHASE.
3. ALL COMPARTMENTS SHALL EXPOSE EXPOSED CONDUIT IN THE COURSE OF THEIR WORK SO AS TO INSURE THAT THEY DO NOT INTERFERE WITH EXISTING SERVICES OR SERVICES FOR FUTURE EXPANSION, AND THAT ALL WIRING SHALL BE PERFORMED IN ACCORD WITH ALL FEDERAL, STATE AND/OR LOCAL RULES, REGULATIONS, STANDARDS AND SAFETY REQUIREMENTS AND ALL OTHER APPLICABLE CODES, RULES AND REGULATIONS THAT MAY APPLY TO THE WORK UNDER THIS CONTRACT. (VLT, CONDUIT, LOCAL SHALL INCLUDE UNDERWRITERS LABORATORY LABELS ON ALL CONDUIT, THE MOST STRINGENT REQUIREMENT SHALL APPLY.)
4. ALL SUPPORTS FOR EQUIPMENT, DEVICES OR FIXTURES SHALL BE UNIFORM FROM THE BUILDING STRUCTURE FROM THE WORK AREA TO THE SUPPORTS TO MAINTAIN PROPER CLEARANCES FROM CEILING, WALLS OR OTHER STRUCTURES.
5. WHERE INSTALLING AN EXISTING CONDUIT OR SERVICE CONDUIT, THE CONTRACTOR SHALL PROVIDE PRELIMINARY ASSESSMENT AND RECOMMENDATION FOR THE PROTECTION OF EXISTING CONDUITS FROM DAMAGE DURING THE WORK.
6. WHERE INSTALLING AN EXISTING CONDUIT OR SERVICE CONDUIT, THE CONTRACTOR SHALL PROVIDE PRELIMINARY ASSESSMENT AND RECOMMENDATION FOR THE PROTECTION OF EXISTING CONDUITS FROM DAMAGE DURING THE WORK.
7. ALL ELECTRICAL COMPONENTS AND EQUIPMENT SHALL BE LABELED BY UNDERWRITERS LABORATORIES OR OTHER LISTED LISTING AGENCY (APPROVED AND LABELING OF REMOVAL COMPONENTS ON AN ASSEMBLY IS NOT ACCEPTABLE AS MEANS THE REQUIREMENT) UNLESS SHOWN BY THE ENGINEER IN WRITING.
8. ALL WIRING SYSTEMS SHALL BE INSTALLED WITH A MINIMUM OF SERVICE CONDUCTORS, WHETHER SINGLE OR PHASE.
9. ALL COMPARTMENTS SHALL EXPOSE EXPOSED CONDUIT IN THE COURSE OF THEIR WORK SO AS TO INSURE THAT THEY DO NOT INTERFERE WITH EXISTING SERVICES OR SERVICES FOR FUTURE EXPANSION, AND THAT ALL WIRING SHALL BE PERFORMED IN ACCORD WITH ALL FEDERAL, STATE AND/OR LOCAL RULES, REGULATIONS, STANDARDS AND SAFETY REQUIREMENTS AND ALL OTHER APPLICABLE CODES, RULES AND REGULATIONS THAT MAY APPLY TO THE WORK UNDER THIS CONTRACT. (VLT, CONDUIT, LOCAL SHALL INCLUDE UNDERWRITERS LABORATORY LABELS ON ALL CONDUIT, THE MOST STRINGENT REQUIREMENT SHALL APPLY.)
10. ALL SUPPORTS FOR EQUIPMENT, DEVICES OR FIXTURES SHALL BE UNIFORM FROM THE BUILDING STRUCTURE FROM THE WORK AREA TO THE SUPPORTS TO MAINTAIN PROPER CLEARANCES FROM CEILING, WALLS OR OTHER STRUCTURES.
11. WHERE INSTALLING AN EXISTING CONDUIT OR SERVICE CONDUIT, THE CONTRACTOR SHALL PROVIDE PRELIMINARY ASSESSMENT AND RECOMMENDATION FOR THE PROTECTION OF EXISTING CONDUITS FROM DAMAGE DURING THE WORK.
12. WHERE INSTALLING AN EXISTING CONDUIT OR SERVICE CONDUIT, THE CONTRACTOR SHALL PROVIDE PRELIMINARY ASSESSMENT AND RECOMMENDATION FOR THE PROTECTION OF EXISTING CONDUITS FROM DAMAGE DURING THE WORK.
13. ALL ELECTRICAL COMPONENTS AND EQUIPMENT SHALL BE LABELED BY UNDERWRITERS LABORATORIES OR OTHER LISTED LISTING AGENCY (APPROVED AND LABELING OF REMOVAL COMPONENTS ON AN ASSEMBLY IS NOT ACCEPTABLE AS MEANS THE REQUIREMENT) UNLESS SHOWN BY THE ENGINEER IN WRITING.
14. ALL WIRING SYSTEMS SHALL BE INSTALLED WITH A MINIMUM OF SERVICE CONDUCTORS, WHETHER SINGLE OR PHASE.
15. ALL COMPARTMENTS SHALL EXPOSE EXPOSED CONDUIT IN THE COURSE OF THEIR WORK SO AS TO INSURE THAT THEY DO NOT INTERFERE WITH EXISTING SERVICES OR SERVICES FOR FUTURE EXPANSION, AND THAT ALL WIRING SHALL BE PERFORMED IN ACCORD WITH ALL FEDERAL, STATE AND/OR LOCAL RULES, REGULATIONS, STANDARDS AND SAFETY REQUIREMENTS AND ALL OTHER APPLICABLE CODES, RULES AND REGULATIONS THAT MAY APPLY TO THE WORK UNDER THIS CONTRACT. (VLT, CONDUIT, LOCAL SHALL INCLUDE UNDERWRITERS LABORATORY LABELS ON ALL CONDUIT, THE MOST STRINGENT REQUIREMENT SHALL APPLY.)
16. ALL SUPPORTS FOR EQUIPMENT, DEVICES OR FIXTURES SHALL BE UNIFORM FROM THE BUILDING STRUCTURE FROM THE WORK AREA TO THE SUPPORTS TO MAINTAIN PROPER CLEARANCES FROM CEILING, WALLS OR OTHER STRUCTURES.
17. WHERE INSTALLING AN EXISTING CONDUIT OR SERVICE CONDUIT, THE CONTRACTOR SHALL PROVIDE PRELIMINARY ASSESSMENT AND RECOMMENDATION FOR THE PROTECTION OF EXISTING CONDUITS FROM DAMAGE DURING THE WORK.
18. WHERE INSTALLING AN EXISTING CONDUIT OR SERVICE CONDUIT, THE CONTRACTOR SHALL PROVIDE PRELIMINARY ASSESSMENT AND RECOMMENDATION FOR THE PROTECTION OF EXISTING CONDUITS FROM DAMAGE DURING THE WORK.
19. ALL ELECTRICAL COMPONENTS AND EQUIPMENT SHALL BE LABELED BY UNDERWRITERS LABORATORIES OR OTHER LISTED LISTING AGENCY (APPROVED AND LABELING OF REMOVAL COMPONENTS ON AN ASSEMBLY IS NOT ACCEPTABLE AS MEANS THE REQUIREMENT) UNLESS SHOWN BY THE ENGINEER IN WRITING.
20. ALL WIRING SYSTEMS SHALL BE INSTALLED WITH A MINIMUM OF SERVICE CONDUCTORS, WHETHER SINGLE OR PHASE.
21. ALL COMPARTMENTS SHALL EXPOSE EXPOSED CONDUIT IN THE COURSE OF THEIR WORK SO AS TO INSURE THAT THEY DO NOT INTERFERE WITH EXISTING SERVICES OR SERVICES FOR FUTURE EXPANSION, AND THAT ALL WIRING SHALL BE PERFORMED IN ACCORD WITH ALL FEDERAL, STATE AND/OR LOCAL RULES, REGULATIONS, STANDARDS AND SAFETY REQUIREMENTS AND ALL OTHER APPLICABLE CODES, RULES AND REGULATIONS THAT MAY APPLY TO THE WORK UNDER THIS CONTRACT. (VLT, CONDUIT, LOCAL SHALL INCLUDE UNDERWRITERS LABORATORY LABELS ON ALL CONDUIT, THE MOST STRINGENT REQUIREMENT SHALL APPLY.)
22. ALL SUPPORTS FOR EQUIPMENT, DEVICES OR FIXTURES SHALL BE UNIFORM FROM THE BUILDING STRUCTURE FROM THE WORK AREA TO THE SUPPORTS TO MAINTAIN PROPER CLEARANCES FROM CEILING, WALLS OR OTHER STRUCTURES.
23. WHERE INSTALLING AN EXISTING CONDUIT OR SERVICE CONDUIT, THE CONTRACTOR SHALL PROVIDE PRELIMINARY ASSESSMENT AND RECOMMENDATION FOR THE PROTECTION OF EXISTING CONDUITS FROM DAMAGE DURING THE WORK.
24. WHERE INSTALLING AN EXISTING CONDUIT OR SERVICE CONDUIT, THE CONTRACTOR SHALL PROVIDE PRELIMINARY ASSESSMENT AND RECOMMENDATION FOR THE PROTECTION OF EXISTING CONDUITS FROM DAMAGE DURING THE WORK.
25. ALL ELECTRICAL COMPONENTS AND EQUIPMENT SHALL BE LABELED BY UNDERWRITERS LABORATORIES OR OTHER LISTED LISTING AGENCY (APPROVED AND LABELING OF REMOVAL COMPONENTS ON AN ASSEMBLY IS NOT ACCEPTABLE AS MEANS THE REQUIREMENT) UNLESS SHOWN BY THE ENGINEER IN WRITING.
26. ALL WIRING SYSTEMS SHALL BE INSTALLED WITH A MINIMUM OF SERVICE CONDUCTORS, WHETHER SINGLE OR PHASE.
27. ALL COMPARTMENTS SHALL EXPOSE EXPOSED CONDUIT IN THE COURSE OF THEIR WORK SO AS TO INSURE THAT THEY DO NOT INTERFERE WITH EXISTING SERVICES OR SERVICES FOR FUTURE EXPANSION, AND THAT ALL WIRING SHALL BE PERFORMED IN ACCORD WITH ALL FEDERAL, STATE AND/OR LOCAL RULES, REGULATIONS, STANDARDS AND SAFETY REQUIREMENTS AND ALL OTHER APPLICABLE CODES, RULES AND REGULATIONS THAT MAY APPLY TO THE WORK UNDER THIS CONTRACT. (VLT, CONDUIT, LOCAL SHALL INCLUDE UNDERWRITERS LABORATORY LABELS ON ALL CONDUIT, THE MOST STRINGENT REQUIREMENT SHALL APPLY.)
28. ALL SUPPORTS FOR EQUIPMENT, DEVICES OR FIXTURES SHALL BE UNIFORM FROM THE BUILDING STRUCTURE FROM THE WORK AREA TO THE SUPPORTS TO MAINTAIN PROPER CLEARANCES FROM CEILING, WALLS OR OTHER STRUCTURES.
29. WHERE INSTALLING AN EXISTING CONDUIT OR SERVICE CONDUIT, THE CONTRACTOR SHALL PROVIDE PRELIMINARY ASSESSMENT AND RECOMMENDATION FOR THE PROTECTION OF EXISTING CONDUITS FROM DAMAGE DURING THE WORK.
30. WHERE INSTALLING AN EXISTING CONDUIT OR SERVICE CONDUIT, THE CONTRACTOR SHALL PROVIDE PRELIMINARY ASSESSMENT AND RECOMMENDATION FOR THE PROTECTION OF EXISTING CONDUITS FROM DAMAGE DURING THE WORK.
31. ALL ELECTRICAL COMPONENTS AND EQUIPMENT SHALL BE LABELED BY UNDERWRITERS LABORATORIES OR OTHER LISTED LISTING AGENCY (APPROVED AND LABELING OF REMOVAL COMPONENTS ON AN ASSEMBLY IS NOT ACCEPTABLE AS MEANS THE REQUIREMENT) UNLESS SHOWN BY THE ENGINEER IN WRITING.
32. ALL WIRING SYSTEMS SHALL BE INSTALLED WITH A MINIMUM OF SERVICE CONDUCTORS, WHETHER SINGLE OR PHASE.
33. ALL COMPARTMENTS SHALL EXPOSE EXPOSED CONDUIT IN THE COURSE OF THEIR WORK SO AS TO INSURE THAT THEY DO NOT INTERFERE WITH EXISTING SERVICES OR SERVICES FOR FUTURE EXPANSION, AND THAT ALL WIRING SHALL BE PERFORMED IN ACCORD WITH ALL FEDERAL, STATE AND/OR LOCAL RULES, REGULATIONS, STANDARDS AND SAFETY REQUIREMENTS AND ALL OTHER APPLICABLE CODES, RULES AND REGULATIONS THAT MAY APPLY TO THE WORK UNDER THIS CONTRACT. (VLT, CONDUIT, LOCAL SHALL INCLUDE UNDERWRITERS LABORATORY LABELS ON ALL CONDUIT, THE MOST STRINGENT REQUIREMENT SHALL APPLY.)
34. ALL SUPPORTS FOR EQUIPMENT, DEVICES OR FIXTURES SHALL BE UNIFORM FROM THE BUILDING STRUCTURE FROM THE WORK AREA TO THE SUPPORTS TO MAINTAIN PROPER CLEARANCES FROM CEILING, WALLS OR OTHER STRUCTURES.
35. WHERE INSTALLING AN EXISTING CONDUIT OR SERVICE CONDUIT, THE CONTRACTOR SHALL PROVIDE PRELIMINARY ASSESSMENT AND RECOMMENDATION FOR THE PROTECTION OF EXISTING CONDUITS FROM DAMAGE DURING THE WORK.
36. WHERE INSTALLING AN EXISTING CONDUIT OR SERVICE CONDUIT, THE CONTRACTOR SHALL PROVIDE PRELIMINARY ASSESSMENT AND RECOMMENDATION FOR THE PROTECTION OF EXISTING CONDUITS FROM DAMAGE DURING THE WORK.
37. ALL ELECTRICAL COMPONENTS AND EQUIPMENT SHALL BE LABELED BY UNDERWRITERS LABORATORIES OR OTHER LISTED LISTING AGENCY (APPROVED AND LABELING OF REMOVAL COMPONENTS ON AN ASSEMBLY IS NOT ACCEPTABLE AS MEANS THE REQUIREMENT) UNLESS SHOWN BY THE ENGINEER IN WRITING.
38. ALL WIRING SYSTEMS SHALL BE INSTALLED WITH A MINIMUM OF SERVICE CONDUCTORS, WHETHER SINGLE OR PHASE.
39. ALL COMPARTMENTS SHALL EXPOSE EXPOSED CONDUIT IN THE COURSE OF THEIR WORK SO AS TO INSURE THAT THEY DO NOT INTERFERE WITH EXISTING SERVICES OR SERVICES FOR FUTURE EXPANSION, AND THAT ALL WIRING SHALL BE PERFORMED IN ACCORD WITH ALL FEDERAL, STATE AND/OR LOCAL RULES, REGULATIONS, STANDARDS AND SAFETY REQUIREMENTS AND ALL OTHER APPLICABLE CODES, RULES AND REGULATIONS THAT MAY APPLY TO THE WORK UNDER THIS CONTRACT. (VLT, CONDUIT, LOCAL SHALL INCLUDE UNDERWRITERS LABORATORY LABELS ON ALL CONDUIT, THE MOST STRINGENT REQUIREMENT SHALL APPLY.)
40. ALL SUPPORTS FOR EQUIPMENT, DEVICES OR FIXTURES SHALL BE UNIFORM FROM THE BUILDING STRUCTURE FROM THE WORK AREA TO THE SUPPORTS TO MAINTAIN PROPER CLEARANCES FROM CEILING, WALLS OR OTHER STRUCTURES.
41. WHERE INSTALLING AN EXISTING CONDUIT OR SERVICE CONDUIT, THE CONTRACTOR SHALL PROVIDE PRELIMINARY ASSESSMENT AND RECOMMENDATION FOR THE PROTECTION OF EXISTING CONDUITS FROM DAMAGE DURING THE WORK.
42. WHERE INSTALLING AN EXISTING CONDUIT OR SERVICE CONDUIT, THE CONTRACTOR SHALL PROVIDE PRELIMINARY ASSESSMENT AND RECOMMENDATION FOR THE PROTECTION OF EXISTING CONDUITS FROM DAMAGE DURING THE WORK.
43. ALL ELECTRICAL COMPONENTS AND EQUIPMENT SHALL BE LABELED BY UNDERWRITERS LABORATORIES OR OTHER LISTED LISTING AGENCY (APPROVED AND LABELING OF REMOVAL COMPONENTS ON AN ASSEMBLY IS NOT ACCEPTABLE AS MEANS THE REQUIREMENT) UNLESS SHOWN BY THE ENGINEER IN WRITING.
44. ALL WIRING SYSTEMS SHALL BE INSTALLED WITH A MINIMUM OF SERVICE CONDUCTORS, WHETHER SINGLE OR PHASE.

GENERAL NOTE
 THE CONTRACTOR MUST REFER TO DRAWING 1 SPECIFICATIONS FOR ALTERNATES THAT MUST BE INCLUDED BY THE CONTRACTOR.

SIGNAL SWITCHES	ITEM	DEVICE MODEL & REFER TO SPEC. IF NONE LISTED	BACKBOX, COVER IF APPLICABLE	MOUNTING HEIGHT (TO BOTTOM OF BOX)	DRAWING SYMBOL
	UPPER SIGNAL SWITCH, 250V, 30A			4'-4"	S
	DOWNER SIGNAL SWITCH, 250V, 30A			4'-4"	S
	UPPER SIGNAL SWITCH, 250V, 30A			4'-4"	S
	DOWNER SIGNAL SWITCH, 250V, 30A			4'-4"	S
	UPPER SIGNAL SWITCH, 250V, 30A			4'-4"	S
	DOWNER SIGNAL SWITCH, 250V, 30A			4'-4"	S

SIGNAL DATA/VOICE/VIDEO	ITEM	DEVICE MODEL & REFER TO SPEC. IF NONE LISTED	BACKBOX, COVER IF APPLICABLE	MOUNTING HEIGHT (TO BOTTOM OF BOX)	DRAWING SYMBOL
	VOICE ALARM SYSTEM, 120V, 15A			10'-0"	
	VOICE ALARM SYSTEM, 120V, 15A			10'-0"	
	VOICE ALARM SYSTEM, 120V, 15A			10'-0"	
	VOICE ALARM SYSTEM, 120V, 15A			10'-0"	
	VOICE ALARM SYSTEM, 120V, 15A			10'-0"	
	VOICE ALARM SYSTEM, 120V, 15A			10'-0"	

SIGNAL SURFACE WEATHER	ITEM	DEVICE MODEL & REFER TO SPEC. IF NONE LISTED	BACKBOX, COVER IF APPLICABLE	MOUNTING HEIGHT (TO BOTTOM OF BOX)	DRAWING SYMBOL
	UPPER SURFACE WEATHER, 120V, 15A			10'-0"	
	DOWNER SURFACE WEATHER, 120V, 15A			10'-0"	
	UPPER SURFACE WEATHER, 120V, 15A			10'-0"	
	DOWNER SURFACE WEATHER, 120V, 15A			10'-0"	
	UPPER SURFACE WEATHER, 120V, 15A			10'-0"	
	DOWNER SURFACE WEATHER, 120V, 15A			10'-0"	

LOCAL SOUND AMPLIFICATION

ITEM	DESCRIPTION	MODEL	HEIGHT	SYMBOL
1	LOCAL SOUND AMPLIFICATION, 120V, 15A		10'-0"	
2	LOCAL SOUND AMPLIFICATION, 120V, 15A		10'-0"	
3	LOCAL SOUND AMPLIFICATION, 120V, 15A		10'-0"	
4	LOCAL SOUND AMPLIFICATION, 120V, 15A		10'-0"	

THE ALARM

ITEM	DESCRIPTION	MODEL	HEIGHT	SYMBOL
1	THE ALARM, 120V, 15A		10'-0"	
2	THE ALARM, 120V, 15A		10'-0"	
3	THE ALARM, 120V, 15A		10'-0"	
4	THE ALARM, 120V, 15A		10'-0"	

SECURITY

ITEM	DESCRIPTION	MODEL	HEIGHT	SYMBOL
1	SECURITY, 120V, 15A		10'-0"	
2	SECURITY, 120V, 15A		10'-0"	
3	SECURITY, 120V, 15A		10'-0"	
4	SECURITY, 120V, 15A		10'-0"	

REGULATIONS

ITEM	DESCRIPTION	MODEL	HEIGHT	SYMBOL
1	REGULATIONS, 120V, 15A		10'-0"	
2	REGULATIONS, 120V, 15A		10'-0"	
3	REGULATIONS, 120V, 15A		10'-0"	
4	REGULATIONS, 120V, 15A		10'-0"	

UNIVERSITY LOFTS - Renovate Academic Facility UK School of Art & Visual Studies

ELECTRICAL LEGEND NOT FOR CONSTRUCTION Job Number: 1205 Date: 03/2013 Drawn By: CEI/CRK Checked By: JMS Revision: XXX

E1.0
 PRE-DESIGN
Omni
 ARCHITECTS
 212 North Upper Street
 Lexington, Kentucky 40507-1001
 p 859.252.6664 f 859.253.2358
 www.omniarchitects.com

This Drawing and the Design shown hereon are the property of Omni Architects. The reproduction, copying or other use of this Drawing or Design without the written consent of Omni Architects is prohibited.

